

---

# Copier accounting system COPYTRON<sup>®</sup> CA 2020

---

- Cost center registration with 999 cost centers
  - Connection to the key-counter-connector of the copier is possible
  - Short-stroke keys (no membrane keys)
  - Enable of the copier is possible with:  
    Cost center number (3 digits) or  
    Pin code (7 digits)
  - One enable relay with a changeover contact
  - Two inputs, which are isolated with bipolar optocouplers
  - LCD display, 2x16 signs, back light
  - EEPROM saves the data at mains failures
  - Time controlled deactivation of the copier
  - Copying limit optional adjustable in steps of 100
  - Total counter and two copy counters for every cost center, total counter for every pin code
  - Serial interface for sending data to a printer or a PC
  - Optional accessories: - mounting bracket  
    - plug-in power supply
- 
- Dimensions:           100 (W) x 195 (H) x 45 (D) in mm
  - Colour:               RAL 9002 (light-grey)
  - Weight:               0,6 kg
  - Operating voltage: 24V DC, 60mA
  - Made in Germany
  - CE-sign



COPYTRON<sup>®</sup> is a registered trademark of HÖR electronic.

## **General description:**

The copier accounting system CA 2020 is a flexible cost center registration. It is connectable to all copiers. The connection is carried out to the key-counter of the copier. The operating voltage can be taken from the copier or from a separate plug-in power supply.

To enable the photocopier a cost center number (3 digits) or a pin code (7 digits) must be entered. An arbitrary number of pin codes can be assigned to every cost center. Group formation is possible through this. The CA 2020 makes it possible to assign copying limits to single cost centers.

Every cost center and every pin code has a total counter. Additionally every cost center has two copy counters (e.g. A4 and A3).